

- Fast & Accurate Readings Instant EC measurements with automatic temperature compensation (ATC) for real conditions
- Easy Calibration Ensures long-term accuracy using standard EC calibration solutions.
- Replaceable Probe Extends device life and reduces cost of ownership.
- Dual Display with Backlight Clear visibility inside greenhouses or outdoor farms.
- IP66 Waterproof Built for field conditions resistant to humidity, splashes, and dust.

TECHNICAL SPECIFICATIONS

| Specification | Details |
|---------------------|--|
| Model | AG-EC Plus |
| Measuring Range | Conductance: 0 ~ 1999 μ S 2.00 ~ 19.99 mS . TDS: 0 ~ 9999 ppm , Temperature: 0 ~ 60 °C |
| Resolution | Conductance: 1 μS (0~1999 μS) 0.01 mS (2.00~19.99 mS) TDS: 1 ppm Temperature: 0.1 °C |
| Accuracy | Conductance, TDS: ±3% F.S ±1 digit Temperature: ±1.0 °C |
| Storage Environment | 0 ~ 60 °C; 85% RH (non-condensing) |
| Units | Conductance: µS, mS TDS: ppm Temperature: °C, °F |
| Protection Level | IP66 |
| Power Source | 2 × 1.5V AAA alkaline batteries |
| Dimensions | 180 × 44 × 44 mm |
| Weight | About 92 g (excluding batteries) |
| Warranty | 12 months |

Contact Us



+64- 94152380



sales@autogrow.com



www.autogrow.com



Seksyen U13 Shas Alam, 40170, Malaysia